

BLANK PAGE



Indian Standard

GUIDE FOR PAPER SPOILAGE AND WASTAGE FOR PRINTING INDUSTRY

PART 1 SHEETFED LETTERPRESS AND OFFSET PROCESSES

UDC 655 02:002:68:655:322 + 655:344

@ Copyright 1988

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard

GUIDE FOR PAPER SPOILAGE AND WASTAGE FOR PRINTING INDUSTRY

PART 1 SHEETFED LETTREPRESS AND OFFSET PROCESSES

Publications and Graphic Technology Sectional Committee, EC 10

Chairman

Зикі М. J. Singн

Members

SHRI R. B. ALVA

SHRI G. D. DHOND (Alternate)

SHRI S. P. AMBASTA

SHRI P. S. SHANKAR (Alternate) SHRI D. N. RAI BHATNAGAR

SHRI M. B. BOBADE

SHRI V. N. CHHABRA

PROF M. R. DUA

SHRI TALEWAR GIRI

SHRI C. L. GUPTA

COL KRISHAN LAL

SHRI VISHVANATH MALHOTRA SHRI KRISHNACHANDER BERI (Alternate)

SHRI ARUN MEHTA

SHRI SUDHIR MEHTA

SHRIS, S. MURTHY

SHRI G. S. SHARMA (Alternate)

SHRI V. V. NAIDU

SHRI G. R. RAO (Alternate)

Representing

Directorate of Printing (Ministry of Urban

Development), New Delhi

Directorate of Government Printing & Stationery,

Government of Maharashtra

Publications and Information Directorate (CSIR),

New Delhi

Punjab National Bank, New Delhi

Government Institute of Printing Technology,

Bombay

The Statesman Ltd, New Delhi

Institute of Mass Communication, Indian

New Delhi

Department of Education (Ministry of Human

Research Development), New Delhi

Directorate of Advertising & Visual Publicity (Ministry of Information & Broadcasting),

New Delhi

The Institution of Engineers (India), Calcutta

All India Hindi Publishers' Association, Varanasi

Vakil & Sons Limited, Bombay

Bennett, Coleman & Co Ltd, New Delhi

Defence Scientific Information & Documentation

Centre (Ministry of Defence), Delhi

A. P. Government Text Book Press, Hyderabad

(Continued on page 2)

© Copyright 1988

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 12000 (Part 1) - 1987

(Continued from page 1)

Members

Representing

SHRI JAIPAL NANGIA

National Council of Educational Research and Training, New Delhi

SHRI C. N. RAO (Alternate)

SHRI D. NARASIMHAIAH

Office of the Director of Printing, Stationery & Publications, Bangalore

SHRI T. SATISH U. PAI

Manipal Power Press, Manipal

SHRI P. BHASKER RAO (Alternate)

DR R. D. PANWAR

College of Vocational Studies, University of Delhi, Delhi

SHRI V. RAMACHANDRAN

Indian National Scientific Documentation Centre (CSIR), New Delhi

SHRI PRADEEP BANERJEE (Alternate) SHRI K. MOHAN RAO

Institute of Printing Technology, Madras

SHRI M. N. SUBRAMANIAN (Alternate) SHRI U. PRABHAKAR RAO

National Book Trust, India, New Delhi

REPRESENTATIVE

Directorate of Printing and Stationery, Government of Uttar Pradesh, Allahabad

Shri A. K. Roy SHRIS, K. SACHDEVA Thomson Press (India) Ltd, New Delhi Federation of Indian Publishers, New Delhi

Shri Mohan Primlani (Alternate) SHRI K. L. SAHGAL

Paper and Its Products (Excluding Packaging Materials) Sectional Committee, CDC 15,

SHRI O. L. DUGGAL (Alternate) SHRI D. SEN

The Regional Institute of Printing Technology, Calcutta

SHRI P. SEN (Alternate) SHRI N. N. SETHI

SHRI V. SETHURAM

Associated Artists, New Delhi

Federation of Master Printers, India New Delhi

SHRI V. K. SINHA GADDE

Pusa Polytechnic (Delhi Administration), New Delhi

SHRI B. D. MENDIRATTA (Alternate) SHRI A. N. SRIDHAR

Air India, Bombay

SHRIH. H. N. TANDON

Publications Division (Ministry of Information and Broadcasting), New Delhi

SHRI TARKESHWAR PRASAD

Northern Regional Institute of Printing Technology, Allahabad

SHRI SHAMIM AHMAD (Alternate) SHRI RAVI VYAS

Macmillan Company of India Limited, New Delhi

SHRI K. C. SHARMA, Director (Pub)

Director General, BIS (Ex-officio Member)

Secretary

SHRIJ. C. GERA Joint Director (Pub), BIS

(Continued on page 9)

Indian Standard

GUIDE FOR PAPER SPOILAGE AND WASTAGE FOR PRINTING INDUSTRY

PART 1 SHEETFED LETTERPRESS AND OFFSET PROCESSES

0. FOREWORD

- 0.1 This Indian Standard (Part 1) was adopted by the Indian Standards Institution on 25 March 1987, after the draft finalized by the Publications and Graphic Technology Sectional Committee had been approved by the Executive Committee.
- 0.2 In printing, binding and other operations, overs should be added to the base quantity of printable papers and boards to allow for make ready, spoilage, etc. The quantity will depend upon the number of colours or workings, closeness of register, length of run, etc and it should include additional allowance for operations like ruling, perforating, numbering, die stamping, overprinting, punching, varnishing, lamination/graining and any additional binding processes or cutwork.
- 0.2.1 It should be noted that before the job is ready for continuous running, a fixed number of sheets are usually spoiled during the process of make-ready, etc regardless of the length of run. Once the machine is set in motion, possible wastage of paper during manufacturing process is considerably reduced and is limited to certain mechanical defects/deficiencies and/or adjustments on machines or to use of materials like ink, paper, plates, etc. Adequate quality control measures, proper maintenance of machinery and competent workers are the factors which reduce wastage of paper to the absolute minimum under normal conditions. In colour work, the allowance must be sufficient to cover wastage due to bad register, defective colour, set off, etc. All this means additional sheets to the base (printable) quantity.
- 0.3 Besides the above, paper gets damaged due to handling during the course of transit from the suppliers to the printers as also during storage. Therefore, proper packaging of paper and board should conform to IS: 6221-1971*.

^{*}Code of practice for packaging of paper and board.

IS: 12000 (Part 1) - 1987

- **0.4** It is necessary to have standard norms for arriving at the admissible spoilage or wastage that has to be allowed for various printing and production jobs which at present is based only on understanding between the print buyers and print sellers (printers).
- 0.5 This standard provides a formula for calculating the spoilage allowance for paper for letterpress and offset printing processes using sheetfed machines. In arriving at this formula, the types of jobs, quality-wise and quantity-wise as also the interests of printers, print buyers and paper manufacturers and various economic considerations have been kept in view.
- **0.6** In the preparation of this standard, assistance has been taken from the following:
 - Spoilage Formula Allowance for spoilage and overs in printing industry, 1976. The All India Federation of Master Printers, New Delhi.
 - Estimating for printers, 9 Ed Revised, 1977. British Printing Industries Federation, London.
- **0.7** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

- 1.1 This standard (Part 1) prescribes the minimum overs that should be added to the base (printable) quantity of paper needed for a particular job to be printed by sheetfed letterpress and offset processes.
- 1.2 This wastage formula should not be applied to paper below 48 gsm including tissue paper, speciality paper and air mail paper since additional wastage is justified for printing on these papers. Wastage formula for such papers could be mutually decided between the printer and the print buyer.

2. TERMINOLOGY

- 2.1 Spoilage/Wastage Unprofitable materials and labour, the cost of which is not usually charged to a specific customer.
- 2.2 Make-ready Make-ready operations are all the operations which are necessary to make the forme print worthy for continuous running,

^{*}Rules for rounding off numerical values (revised).

- 2.3 Fixed Wastage The wastage involved in make-ready process prior to running on.
- **2.4 Running Wastage** The wastage which occurs during running on subsequent to make-ready.
- 2.5 Printable Quantity Paper may get damaged due to handling during transit and also during storage. Printable quantity of paper would be the actual quantity of paper available to the printer for carrying out the printing. This may be different from the normal number of sheets in a standard ream/packet. The printable quantity of paper would not include paper that may be damaged during handling, transportation and storage prior to the receipt of paper by the printer.
- 2.6 Working Sheet Working sheet is the actual size of paper being used on the machine for printing.
- 2.7 Common Work Work of average quality such as commonly used forms, cheaper additions of books, hand bills, etc, normally printed in single colour.
- 2.8 Close Registration Work Work of high quality, generally printed in multi-colours, containing process colour pictures and illustrations requiring dot-to-dot registration between each colour and high degree of sharpness of image and uniformity of inking and impression throughout the print run.

3. RATIONALE FOR COMPUTING PAPER SPOILAGE ALLOWANCE

- **3.1** The rationale in adopting the formulae for paper spoilage envisages the following:
 - a) A fixed number of sheets (if irreducible, minimum number) are required at initial stages for various operations like make-ready, regardless of the quantity to be printed;
 - b) Paper spoilage depends on the extent and nature of work;
 - c) Wastage of sheet occurs during running/manufacturing process on account of some defects/deficiencies/adjustments on impressions, paper stock or material;

IS: 12000 (Part 1) - 1987

- d) The larger the overall number of copies printed, the lesser is the percentage of spoilage in any continuous print job;
- e) There is a progressive increase in the total number of working sheets towards allowance for spoilage with increase of print order in different slabs;
- f) The spoilage allowance shall be computed on the basis of fixed number of working sheets for minimum make-ready and for the initial print order of 1 000 copies and fixed percentage using slab system for the running waste per colour, per side, for subsequent print order;
- g) Extra spoilage for every additional operation like perforating, varnishing, numbering, etc, shall be provided;
- h) Wherever machine proofs are required, additional wastage on the basis of minimum make-ready shall be provided; and
- Spoilage allowance shall be computed on printable quantity of paper.
- 3.1.1 Allowable wastage for sheetfed letterpress process and offset process has been explained in 4.

4. ALLOWABLE WASTAGE—SHEETFED LETTERPRESS/OFFSET PROCESS

4.1 Tables 1 and 2 give the allowable wastage per side per colour to be added to the base quantity of paper in case of sheetfed letterpress/offset process using the slab system.

TABLE 1 ALLOWABLE WASTAGE, PER SIDE, PER COLOUR FOR COMMON WORK SHEETFED LETTERPRESS PROCESS

(Clause 4.1)

Slab No.	No. of Impressions	Allowable Wastage, Working Sheets
(1)	(2)	(3)
1	Up to 1000	25
2	1 001 - 5 000	25+2-0 percent of slab 2
3	5 001 - 10 000	25+2.0 percent of slab $2+1.25$ percent of slab 3
4	10 001 - 25 000	25+2.0 percent of slab 2+1.25 percent of slab 3+1.0 percent of slab 4
5	25 001 - 50 000	$25+2^{\circ}0$ percent of slabe $2+1^{\circ}25$ percent of slab $3+1^{\circ}0$ percent of slab $4+0^{\circ}75$ percent of slab 5
6	50 001 onwards	25+2.0 percent of slab 2+1.25 percent of slab 3+1.0 percent of slab 4+0.75 percent of slab 5+0.5 percent of slab 6

Example:

Spoilage Allowance for Common Work (Sheetfed Letterpress Process)

No. of impressions: 32 000

Up to 1 000 impressions: 25 w (including make-ready)

25 working sheets

For additional 4 000 impressions:

80 working sheets (2.0 percent)

For additional 5 000 impressions:

62.5 working sheets (1.25 percent)

For additional 15 000 impressions:

150 working sheets (1.0 percent)

For additional 7 000 impressions:

52.5 working sheets (0.75 percent)

For

32 000 impressions: 370 working sheets

Note—The above wastage is expected to cover the wastage for normal binding operations like folding, gathering, collating, stitching/sewing/pasting, trimming, etc. and hence no additional wastage need be given for these operations. However additional wastage for cutwork and other special operations like ruling, perforating, numbering, die stamping, foil printing, punching, etc. may be settled between the print buyer and the printer. Varnishing/lamination/graining may be treated as printing and wastage allowed as for normal printing (impression).

TABLE 2 ALLOWABLE WASTAGE, PER SIDE, PER COLOUR FOR CLOSE REGISTER LETTERPRESS, AND COMMON WORK AND CLOSE REGISTER OFFSET PROCESSES

(Clause 4.1)

SLAB No.	No. of Impressions	Allowable Wastage, Working Sheets
(1)	(2)	(3)
1	Up to 1000	40
2	1 001 - 5 000	40+2.5 percent of slab 2
3	5 001 - 10 000	40+2.5 percent of slab $2+1.75$ percent of slab 3.
4	10 001 - 25 000	40+2.5 percent of slab 1+1.75 percent of slab 3+1.5 percent of slab 4
5	25 001 - 50 000	40+2.5 percent of slab 2+1.75 percent of slab 3+ 1.5 percent of slab 4+1.0 percent of slab 5
6	50 001 onwards	40+2.5 percent of slab 2+1.75 percent of slab 3+1.5 percent of slab 4+1.0 percent of slab 5+0.75 percent of slab 6

Example:

Spoilage Allowance for Work Requiring Close Register (Containing Process Colour Work) Sheetfed Letterpress Common Work as well as Close Register Offset Process

No. of impressions: 32 000

1 000 impressions: 40 working sheets (including make-ready)

For additional 4 000 impressions: 100 working sheets (2.5 percent)

For additional 5 000 impressions: 87.5 working sheets

(1.75 percent)

For additional 15 000 impressions: 225'0 working sheets (1.5 percent)

For additional 7 000 impressions: 70.0 working sheets

(1.0 percent)

For 32 000 impressions: 522.5 working sheets or 523 working sheets

NOTE — The above wastage is expected to cover the wastage for normal binding operations like folding, gathering, collating, stitching/sewing/pasting, trimming, etc and hence no additional wastage need be given for these operations. However, additional wastage for cutwork and other special operations like ruling, perforating, numbering, die stamping, foil printing, punching, etc, may be settled between the print buyer and the printer. Varnishing/lamination/graining may be treated as printing and wastage allowed as for normal printing (impression).

(Continued from page 2)

Spoilage Formula for Paper Subcommittee, EC 10:5

(:0			

SHRI C. N. RAO

Members

SHRI V. N. CHHABRA SHRI S. J. DUBEY

SHRI C. L. GUPTA

SHRI M. L. GUPTA SHRI JAHAR MAJUMDAR SHRI MOHAN MAKHIJANI

SHRI S. N. MEHTA SHRI B. D. MENDIRATTA

SHRI D. NARASIMHAIAH

SHRI NARENDRA KUMAR SHRI S. N. MEHTA (Alternate) SHRI U. PRABHAKAR RAO SHRI V. SUBRAMANIAN

SHRI JAIPAL SINGH (Alternate) SHRI J. S. VIRDI

SHRI VISHWA NATH

Representing

National Council of Educational Research and Training, New Delhi

The Statesman, New Delhi

Delhi University Press, University of Delhi,

Directorate of Advertising & Visual Publicity (Ministry of Information & Broadcasting), New Delhi

Children's Book Trust, New Delhi

Indian Paper Makers' Association, Calcutta
The Federation of Publishers & Booksellers
Associations in India, New Delhi

Mehta Offset Works, New Delhi

Polytechnic (Delhi Administration), Pusa New Delhi

Office of the Director of Printing, Stationery & Publications, Bangalore

The Federation of Indian Publishers, New Delhi

National Book Trust, India, New Delhi All India Federation of Master Printers, New Delhi

Directorate of Printing (Ministry of Urban Development), New Delhi Raipal & Sons, Delhi

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

Pressure, stress

Quantity	Unit	Symbol	
Length	metre	m	
Mass	kilogram	kg	
Time	second	8	
Electric current	ampere	A	
Thermodynamic temperature	kelvin	К	
Luminous intensity	candela	cd	
Amount of substance	mole	mol	
Supplementary Units			
Quantity	Unit	Symbol	
Plane angle	radian	rad	
Solid angle	steradian	er	
Derived Units			
Quantity	Unit	Sym b ol	Definition
Force	newton	N	1 N == 1 kg.m/s
Energy	joule	J	1 J = 1 N.m
Power	watt	W	1 W == 1 J/s
Flux	weber	Wb	1 Wb = 1 V.s
Flux density	tesla	T	1 T = 1 Wb/m ²
Frequency	hertz	Hz	1 Hz = 1 c/s (s ⁻¹)
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	V	1 V = 1 W/A

pascal

Pa